

# DINARA OIL®

*Vaš kod za ulja i maziva*

## TECHNICAL INFORMATIONS ABOUT THE PRODUCT FLUID FOR COOLING SYSTEMS OF ENGINES - ANTIFREEZE

### ANTIFREEZE DINARKO -40

**ANTIFREEZE DINARKO -40** is a liquid used as a protection for motor vehicle cooling systems from freezing and corrosion, based on monoethylene glycol (MEG) and corrosion inhibitors. It is a final product and provides protection up to -38°C.

Advantages:

- provides excellent protection against rust and cavitation;
- transmits heat well, does not foam;
- it is inert to sealants, does not damage cooling system hoses.

**QUALITY LEVEL: SRPS H.Z2.010, tip 3; BS 6580; ASTM D 3306; AFNOR NF R 15-601; SAE J 1034**

### PHYSICAL - CHEMICAL CHARACTERISTICS

Characteristics	Units	Typical values	Test methods
Density at 20°C	g/cm <sup>3</sup>	1,106 - 1,108	SRPS EN ISO 3675
Color	-	blue	Visually
Boiling point, min	°C	110	SRPS H.Z8.058
Corrosion of metals in glass apparatus	mg	satisfies	SRPS H.Z8.056
pH - value	-	7,5-8,5	SRPS H.Z8.052
Freezing point, min	°C	-38	SRPS H.Z8.053

### PURPOSE

**ANTIFREEZE DINARKO -40** is used for cooling systems of engines with watercooling mechanism and for central heating systems. Provides maximum protection against freezing and overheating, corrosion and scale formation. Replacement period is 2 years or after 50 000 km.

### STORAGE

**ANTIFREEZE DINARKO -40** - should be stored in their original packaging protected from the direct influence of the atmosphere.

### PACKAGING:

1 L	5 L	10 L	20 L	220 kg	1000 L
x 15 pcs	x 3 pcs	x 2 pcs	x	x	x