

DINARA[®] OIL[®]

Vaš kod za ulja i maziva

TECHNICAL INFORMATIONS ABOUT THE PRODUCT AUTOMATIC TRANSMISSION FLUID (ATF)

ATF D II

ATF D II is a high quality mineral oil for the lubrication of automatic transmission systems, servo and hydraulic steerings where the use of oil with GM DEXRON IID quality level is recommended.

Advantages:

- good thermal and oxidation stability, stable viscosity;
- provides good corrosion protection;
- has an excellent low temperature properties;
- does not foam and has excellent air extraction capability.

QUALITY LEVEL: GM DEXRON IID; MB 236.1/236.6/236.7/236.9; MAN 339-D; VOITH G 607(H55.6335.36); ALLISON C-4; CATERPILLAR TO-2; ZF TE-ML 03D/04D/14A/17C

PHYSICAL - CHEMICAL CHARACTERISTICS

Characteristics	Units	Typical values	Test methods
Density on 15 °C	g/cm ³	0,87	SRPS EN ISO 3675
Color	-	red	Visually
Kinetic viscosity at 100 °C	mm ² /s	37	SRPS ISO 3104
Kinetic viscosity at 40 °C	mm ² /s	7,1-7,5	SRPS ISO 3104
Viscosity index	-	160-170	SRPS ISO 2909
Point of ignition, COC	°C	210	SRPS ISO 2592
Pour point	°C	-42	SRPS ISO 3016

PURPOSE

ATF D II is a premium multifunction transmission oil for power transmission and lubrication of automatic gears, power steerings and torque converter for motor vehicles, agricultural and construction machinery and other equipment. It can also be used with hydraulic steering, hydraulic couplings and hydraulic transmission systems where the manufacturer recommends GM Dexron IID oil quality level.

STORAGE

ATF D II - should be stored in their original packaging protected from the direct influence of the atmosphere.

PACKAGING:

0.5 L	1 L	10 L	20 L	200 L	1000 L
	x 15 pcs	x 2 pcs		x	x