

DINARA OIL®

Vaš kod za ulja i maziva

TECHNICAL INFORMATIONS ABOUT THE PRODUCT SEMI-SYNTHETIC TRANSMISSION FLUID

DINOL GETRIBE OIL POLUSINT 75W90

DINOL GETRIBE OIL POLUSINT 75W90 is a high quality semi-synthetic oil specially designed for gears of light and heavy commercial vehicles and equipment operating in harsh operating conditions. Unique additive technology allows the use of one lubricant in the rear axles of synchronized and unsynchronized manual transmission.

Advantages:

- high thermal and oxidation stability;
- outstanding performance at low temperatures;
- great "Shear" stability;
- excellent tribological properties provide reduced fuel consumption and extended replacement interval.

QUALITY LEVEL: API GL-4/GL-5, MIL-L-PRF-2105E; API MT-1; Mack GO-J; MAN 341 Type Z2; MAN 341 Type M2; MB 235.0; Scania STO-1; SAE J 2360; Arvin Meritor 0-76-N; ZF TE-ML 02B,05A,07A,08

PHYSICAL - CHEMICAL CHARACTERISTICS

Characteristics	Units	Typical values	Test methods
Density on 15 °C	g/cm ³	0.878	SRPS EN ISO 3675
Kinetic viscosity at 100 °C	mm ² /s	15.2	SRPS ISO 3104
Kinetic viscosity at 40 °C	mm ² /s	94.2	SRPS ISO 3104
Viscosity index	-	171	SRPS ISO 2909
Point of ignition, COC	°C	>201	SRPS ISO 2592
Pour point	°C	-36	SRPS ISO 3016
Viscosity at -40 °C (Brookfield)	cP	150000	ASTM D 2983

PURPOSE

DINOL GETRIBE OIL POLUSINT 75W90 is used for the lubrication of all types of hypoid gears of motor vehicles and industrial machines, which operate at high loads as well as at high temperature changes. It can also be used for the lubrication of manual gears of passenger cars, light and heavy commercial vehicles, as well as for agricultural, construction and mining machinery.

STORAGE

DINOL GETRIBE OIL POLUSINT 75W90 - should be stored in their original packaging protected from the direct influence of the atmosphere.

PACKAGING:

1 L	5 L	10 L	20L	200 L	1000 L
x 15 pcs			x	x	