

# DINARA OIL®

*Vaš kod za ulja i maziva*

## TECHNICAL INFORMATIONS ABOUT THE PRODUCT 100% SYNTHETIC TRANSMISSION FLUID

### DINOL GETRIBE OIL TX 75W80

**DINOL GETRIBE OIL TX 75W80** is a high quality synthetic oil for manual gears of passenger commercial vehicles with extended oil change interval. It is characterized by high thermal stability and excellent lubrication which reduces fuel consumption. It is used for the manual transmission of vehicles equipped with a variety of synchronizers, including those based on carbon.

Advantages:

- high thermal and oxidation stability;
- outstanding performance at low temperatures;
- excellent tribological properties provide reduced fuel consumption and extended replacement interval.

**QUALITY LEVEL: API GL-5, MAN 341 Z4, MAN 341 E3, Iveco, Renault B0032/2, Eaton Europe, VOLVO 97305, MB 235.4, ZF TE-ML 01L,02L,08,16K**

### PHYSICAL - CHEMICAL CHARACTERISTICS

| Characteristics                  | Units              | Typical values | Test methods     |
|----------------------------------|--------------------|----------------|------------------|
| Density on 15 °C                 | g/cm <sup>3</sup>  | 0.86           | SRPS EN ISO 3675 |
| Kinetic viscosity at 100 °C      | mm <sup>2</sup> /s | 9,8            | SRPS ISO 3104    |
| Kinetic viscosity at 40 °C       | mm <sup>2</sup> /s | 58,5           | SRPS ISO 3104    |
| Viscosity index                  | -                  | 155            | SRPS ISO 2909    |
| Point of ignition, COC           | °C                 | >201           | SRPS ISO 2592    |
| Pour point                       | °C                 | -39            | SRPS ISO 3016    |
| Viscosity at -40 °C (Brookfield) | cP                 | 150000         | ASTM D 2983      |

### PURPOSE

**DINOL GETRIBE OIL TX 75W80** is used for the lubrication of all types of hypoid gears of motor vehicles and industrial machines which operate under of high impact load conditions as well as under conditions of high temperature changes. It can also be used for the lubrication of manual transmissions of passenger cars, light and heavy commercial vehicles, as well as for agricultural, construction and mining machinery.

### STORAGE

**DINOL GETRIBE OIL TX 75W80** - should be stored in their original packaging protected from the direct influence of the atmosphere.

### PACKAGING:

| 1 L      | 5 L | 10 L | 20L | 200 L | 1000 L |
|----------|-----|------|-----|-------|--------|
| x 15 pcs |     |      | x   | x     |        |