

DINARA[®] OIL[®]

Vaš kod za ulja i maziva

TECHNICAL INFORMATIONS ABOUT THE PRODUCT OIL FOR TWO-STROKE ENGINES

TWO-STROKE FOR CHAINSOWS

TWO-STROKE FOR CHAINSOWS is an engine oil for the lubrication of new generation high performance two-stroke engines like: STIHL, DOLMAR, HUSQUARNA, TOMOS, PARTNER-FARMER, etc.

The high quality mineral base oil provides efficient application in modern STIHL 2-stroke engines, primarily air-cooled (separate or blend).

Provides excellent lubrication, wear protection and extends life of the engine. Reduces soot and sludge in exhaust systems.

Advantages:

- provides excellent lubrication and wear protection;
- extends life of the engine;
- reduces soot and sludge in exhaust systems;
- good compatibility with sealing materials;
- mixes well with gasoline.

QUALITY LEVEL: API TC (ASTM TSC-3); JASO FC; SRPS ISO 6743 - 15; ISO-L-EGC, SRPS ISO 13738 (L-EGC)

PHYSICAL - CHEMICAL CHARACTERISTICS

Characteristics	Units	Typical values	Test methods
Density at 15 °C	g/cm ³	0,880-0,890	SRPS EN ISO 3675
Kinetic viscosity at 100°C	mm ² /s	12,3	SRPS ISO 3104
Point of ignition, COC	°C	220	SRPS ISO 2592
Pour point	°C	-20	SRPS ISO 3016
Sulfate ash	% m/m	0.08	SRPS ISO 3987

PURPOSE

TWO-STROKE FOR CHAINSOWS is recommended primarily for the lubrication of air-cooled two-stroke STIHL engines in all climate conditions. Provides good engine performance for long periods of operation, mixes well with gasoline. In accordance with STIHL recommendation, it could be mixed with all types of unleaded gasoline in a ratio of 1:50 (2% oil).

STORAGE

TWO-STROKE FOR CHAINSOWS - should be stored in their original packaging protected from the direct influence of the atmosphere.

PACKAGING:

100 ml	1 L	10 L	20 L	200 L	1000 L
x 80 pcs	x 15 pcs	x 2 pcs		x	x