

DINARA OIL®

Vaš kod za ulja i maziva

TECHNICAL INFORMATIONS ABOUT THE PRODUCT SEMI-SYNTHETIC OIL FOR PASSENGER VEHICLES

FAVORIT-2 SAE 10W40

FAVORIT-2 SAE 10W40 is a high performance semi-synthetic multigrade engine oil for the lubrication of the most modern gasoline and diesel engines of passenger and light commercial vehicles, including turbocharged engines with multi-valve and computer gasoline injection, with and without catalytic converters. Meets the requirements of direct injection engines. It is used in all driving conditions and all seasons.

Advantages:

- high performances;
- provides effective engine protection against wear in cold operating conditions;
- provides corrosion resistance in extreme operating conditions with maximum engine power output;
- low volatility.

QUALITY LEVEL: API SL/CF, ACEA A3/B3/B4-12, ISO 6743-15; ISO L-E; MB 229.1/229.3, VW 501.01/502.00/505.00, Renault RN 0700 /0710, PSA B71 2300

PHYSICAL - CHEMICAL CHARACTERISTICS

Characteristics	Units	Typical values	Test methods
Density on 15 °C	g/cm ³	0,88	SRPS EN ISO 3675
Kinetic viscosity at 100 °C	mm ² /s	14-14,5	SRPS ISO 3104
Viscosity index	-	145	SRPS ISO 2909
Point of ignition, COC	°C	220	SRPS ISO 2592
Pour point	°C	-35	SRPS ISO 3016
Total base number (TBN)	mgKOH/g	10	SRPS ISO 3771
Foaming, max sequence I, sequence I, sequence III	mL/mL	10/0 50/0 10/0	SRPS ISO 6247

PURPOSE

FAVORIT-2 SAE 10W40 is a semi-synthetic multigrade engine oil used for the lubrication of modern gasoline and diesel engines of passenger and light commercial vehicles, with and without catalytic converters. It is suitable for EURO 3 engines.

Oil change is done according to the manufacturer's recommendations, but the common recommendation is after 15 000 km.

STORAGE

FAVORIT-2 SAE 10W40 - should be stored in their original packaging protected from the direct influence of the atmosphere.

PACKAGING:

1 L	4 L	5 L	10 L	20 L	200 L	1000 L
x 15 pcs	x 3 pcs	x 3 pcs			x	x