

# DINARA OIL®

*Vaš kod za ulja i maziva*

## TECHNICAL INFORMATIONS ABOUT THE PRODUCT MOTOR OIL FOR PASSENGER VEHICLES

### GAS OIL SAE 15W40

**GAS OIL SAE 15W40** is a special multigrade mineral engine oil with viscosity gradation 15W40 for the lubrication of passenger vehicles with liquid petroleum gas or gasoline engines.

Provides good protection against sludge and effectively protects the engine from wear and corrosion.

Advantages:

- ensures reliable operation of the engine under normal operating conditions;
- provides good protection against sludge;
- effectively protects the engine from wear and corrosion;
- good oxidative and thermal stability and low oil consumption.

**QUALITY LEVEL: API SL/CF, ACEA A3/B3**

### PHYSICAL - CHEMICAL CHARACTERISTICS

Characteristics	Units	Typical values	Test methods
Density on 15 °C	g/cm <sup>3</sup>	0,88	SRPS EN ISO 3675
Kinetic viscosity at 100 °C	mm <sup>2</sup> /s	14,5	SRPS ISO 3104
Viscosity index	-	130	SRPS ISO 2909
Point of ignition, COC	°C	220	SRPS ISO 2592
Pour point	°C	-35	SRPS ISO 3016
Total base number (TBN)	mgKOH/g	6,5	SRPS ISO 3771
Foaming, max sequence I, sequence I, sequence III	mL/mL	0/0 20/0 0/0	SRPS ISO 6247

### PURPOSE

**GAS OIL SAE 15W40** is used for the lubrication of gasoline engines of passenger vehicles with LPG (liquid petroleum gas). Its use provides lower oil consumption, extended drain intervals and better engine performance conditions. Oil change is done according to the vehicle manufacturer's recommendations, but the common recommendation is 10 000 km.

### STORAGE

**GAS OIL SAE 15W40** - should be stored in their original packaging protected from the direct influence of the atmosphere.

### PACKAGING:

1 L	5 L	10 L	20 L	200 L	1000 L
x 15 pcs	x 3 pcs			x	x