

DINARA[®] OIL[®]

Vaš kod za ulja i maziva

TECHNICAL INFORMATIONS ABOUT THE PRODUCT OILS FOR MECHANICAL GEARBOXES AND DIFFERENTIALS

GETRIBE OIL SAE 90 GL-4

GETRIBE OIL SAE 90 GL-4 is a mineral monograde oil for the lubrication of mechanical gearboxes and differentials of the vehicles that require API GL-4 quality level.

Advantages

- provides efficient lubricating;
- has a stable viscosity, good oxidation and thermal stability;
- provides protection against rust and corrosion.

QUALITY LEVEL: API GL-4

PHYSICAL - CHEMICAL CHARACTERISTICS

Characteristics	Units	Typical values	Test methods
Density on 15 °C	g/cm ³	0,90	SRPS EN ISO 3675
Kinetic viscosity at 100 °C	mm ² /s	17,5	SRPS ISO 3104
Viscosity index	-	95	SRPS ISO 2909
Point of ignition, COC	°C	220	SRPS ISO 2592
Pour point	°C	-21	SRPS ISO 3016
Foaming, max sequence I, sequence I, sequence III	mL/mL	0/0 0/0 0/0	SRPS ISO 6247
Corrosity (Cu paper, 3h, 100°C)	class	1	SRPS ISO 2160

PURPOSE

GETRIBE OIL SAE 90 GL-4 is a mineral oil for the lubrication of spiral - conical and hypoid gears and certain types of synchronized manual transmission in motor vehicles operating under medium load conditions.

STORAGE

GETRIBE OIL SAE 90 GL-4 - should be stored in their original packaging protected from the direct influence of the atmosphere.

PACKAGING:

1 L	5 L	10 L	20 L	200 L	1000 L
x 15 pcs	x 3 pcs	x 2 pcs	x	x	x