

DINARA OIL®

Vaš kod za ulja i maziva

TECHNICAL INFORMATION ABOUT THE PRODUCT OILS FOR MECHANICAL GEARBOXES AND DIFFERENTIALS

GETRIBE OIL PREMIUM SAE 80W90 GL-5, SAE 85W90 GL-5

GETRIBE OIL PREMIUM SAE 80W90 GL-5, SAE 85W90 GL-5 are a high quality multigrade hypoid mineral oils for the lubrication of mechanical gears and differentials of heavy passenger and commercial vehicles, which operate at high speeds and high load conditions.

Advantages:

- high thermal and oxidation stability;
- protects from the rust and cavitation;
- extends the service life of equipment;
- does not foam and it is inert to sealing elements.

QUALITY LEVEL: API GL-5, MB 235.0, MIL-L-2105D, DAF, MAN 342 M-1, Renault, Voith 3.325-339, Volvo 97310/97316, ZF TE-ML 05C/07A/08/12C/16B/16C/16D/16E/17B/19B/21A/21C

PHYSICAL - CHEMICAL CHARACTERISTICS

Characteristics	Units	Typical values		Test methods
		80W90 GL-5	85W90 GL-5	
Density on 15 °C	g/cm ³	0.89	0.89	SRPS EN ISO 3675
Kinetic viscosity at 100 °C	mm ² /s	15-17	13.5-16	SRPS ISO 3104
Viscosity index	-	110	110	SRPS ISO 2909
Point of ignition, COC, min	°C	190	200	SRPS ISO 2592
Pour point	°C	-27	-21	SRPS ISO 3016

PURPOSE

GETRIBE OIL PREMIUM SAE 80W90 GL-5, SAE 85W90 GL-5 are used for the lubrication of gear drives of power and movement of loaded commercial vehicles and other machines exposed to extreme pressures and shock loads. Such assemblies are hypoid gears, worm shafts, differentials and similar transmissions which do not have non-ferrous metal parts in their assemblies.

STORAGE

GETRIBE OIL PREMIUM SAE 80W90 GL-5, SAE 85W90 GL-5 - should be stored in their original packaging protected from the direct influence of the atmosphere.

PACKAGING:

1 L	5 L	10 L	20L	200 L	1000 L
x 15 pcs	x	x 2 pcs	x	x	x