

DINARA[®] OIL[®]

Vaš kod za ulja i maziva

TECHNICAL INFORMATIONS ABOUT THE PRODUCT MOTOR OILS FOR COMMERCIAL VEHICLES

CLASSIC D SAE 15W40, SAE 20W50

CLASSIC D SAE 15W40, SAE 20W50 are a mineral multigrade engine oils, intended for the lubrication of all types of high-speed diesel engines, with and without turbocharging, operating under normal and heavy duty conditions. **CLASSIC D SAE 20W50** is recommended for engines with high oil consumption.

They reduce engine wear, sludge and varnish, ensuring engine cleanliness. Effectively protect the engine from corrosion.

Advantages:

- ensures reliable operation of the engine under normal operating conditions;
- reduces engine wear, formation of deposits and varnishes, which ensures engine cleanliness;
- effectively protect the engine from corrosion.

QUALITY LEVEL: API CF/SF, CCMC D2 MIL-L-2104C, MB228.0, MAN 270

PHYSICAL - CHEMICAL CHARACTERISTICS

Characteristics	Units	Typical values		Test methods
		15W40	20W50	
Density on 15 °C	g/cm ³	0,88	0,89	SRPS EN ISO 3675
Kinetic viscosity at 100 °C	mm ² /s	14,5	18,5	SRPS ISO 3104
Viscosity index	-	135	130	SRPS ISO 2909
Point of ignition, COC	°C	220	230	SRPS ISO 2592
Pour point	°C	-35	-27	SRPS ISO 3016
Total base number (TBN)	mgKOH/g	9	9	SRPS ISO 3771
Foaming, max sequence I, sequence I, sequence III	mL/mL	10/0 50/0 10/0	10/0 50/0 10/0	SRPS ISO 6247

PURPOSE

CLASSIC D SAE 15W40, SAE 20W50 are an engine oils for the lubrication of diesel engines of commercial vehicles with older classic structures which are operating under the normal and in harsh working conditions. Oil change is done according to the vehicle manufacturer's recommendations, but the common recommendation is 10 000 km.

STORAGE

CLASSIC D SAE 15W40, SAE 20W50 - should be stored in their original packaging protected from the direct influence of the atmosphere.

PACKAGING:

1 L	5 L	10 L	20 L	200 L	1000 L
		x 2 pcs	x	x	x