

# DINARA<sup>®</sup> OIL<sup>®</sup>

*Vaš kod za ulja i maziva*

## TECHNICAL INFORMATIONS ABOUT THE PRODUCT INDUSTRIAL OILS – OIL FOR CHAINS OF CHAINSAWS

### LANCOL UNIVERSAL 100

**LANCOL UNIVERSAL 100** is a mineral oil for the lubrication of chains of various manufacturers' chainsaws in normal and hard working conditions.

It has ability to adhere to the metal sliding surfaces of the chains as well as good water suppression from the metal surfaces. It has excellent anti-wear and lubrication properties and provides effective corrosion protection.

Advantages:

- ability to adhere to the metal sliding surfaces of the chains;
- good water suppression from the metal surfaces;
- excellent anti-wear and lubrication properties;
- effective corrosion protection.

**QUALITY LEVEL: ISO 6743-1 (L-AC)**

#### PHYSICAL - CHEMICAL CHARACTERISTICS

Characteristics	Units	Typical values	Test methods
Density at 15 °C	g/cm <sup>3</sup>	0.88	SRPS EN ISO 3675
Kinetic viscosity at 40 °C	mm <sup>2</sup> /s	100	SRPS ISO 3104
Point of ignition, COC	°C	220	SRPS ISO 2592
Pour point, max	°C	-15	SRPS ISO 3016

#### PURPOSE

**LANCOL UNIVERSAL 100** is an oil for the lubrication of chains of all types of chainsaws used in normal and hard working conditions such as low and high temperatures, in the presence of water, dust and mud.

It should not be used to blend with the fuel for chainsaws powering - oil for two-stroke engines is used for this purpose.

#### STORAGE

**LANCOL UNIVERSAL 100** - should be stored in their original packaging protected from the direct influence of the atmosphere.

#### PACKAGING:

1 L	2 L	5 L	10 L	20 L	200 L	1000 L
x 15 pcs	x 9 pcs	x 3 pcs	x 2 pcs	x	x	x