

DINARA[®] OIL[®]

Vaš kod za ulja i maziva

TECHNICAL INFORMATIONS ABOUT THE PRODUCT LUBRICATING GREASES – LITHIUM EP GREASE

LITOL-24 EP 2

LITOL-24 EP 2 is a lithium EP lubricating grease for the lubrication of roller and sliding bearings at high loads and lower RPMs. Temperature range of application is from -40°C to + 120°C.

Advantages:

- excellent mechanical and oxidation stability;
- good resistance to water and moisture;
- good rheological properties (good lubrication in different temperature conditions);
- anti-corrosion properties.

QUALITY LEVEL: ISO 6743-9 (L-XCCHB 2); DIN 51825; DIN 51502 (K P 2K - 30); SRPS B.H3.624.

PHYSICAL - CHEMICAL CHARACTERISTICS

Characteristics	Units	Typical values	Test methods
Appearance, color	-	homogeneous, yellow - brown	Visually
NLGI consistency	-	2	-
Type of soap (thickener)		Li	-
Penetration at 25 °C after 60 cycles	mm/10	265-295	SRPS ISO 2137
Drop point	°C	> 180	SRPS ISO 2176
Oil extraction	%	12	DIN 51 807/1
Temperature interval of application	°C	- 40 do + 120	-
ISO classification	-	L-XCCHB 2	-
DIN classification	-	K P 2K - 30	-

PURPOSE

LITOL-24 EP 2 lubricating grease is recommended for the lubrication of bearings, slideways, joints, gear couplings and other lubricating assemblies on excavators, presses, rolling mills and other industrial equipment.

STORAGE

LITOL-24 EP 2 - should be stored in their original packaging protected from the direct influence of the atmosphere.

PACKAGING:

0.8 kg	4 kg	5 kg	15 kg	17 kg	180 kg
	x				x