

DINARA[®] OIL[®]

Vaš kod za ulja i maziva

TECHNICAL INFORMATIONS ABOUT THE PRODUCT LUBRICATING GREASES – LITHIUM GREASE

LITOL-24

LITOL-24 is a multi-purpose antifriction waterproof lithium lubricating grease with mineral base. Extremely high quality grease which, due to its performance characteristics, has a very wide range of application, at different loads and temperatures.

Advantages:

- excellent mechanical and oxidative stability – width range of application;
- good adhesion and solidity of lubrication film, which guarantees high lubrication safety and long service life of lubricated assemblies;
- good rheological properties;
- excellent anti-corrosion properties.

QUALITY LEVEL: ISO 6743-9; DIN 51825; DIN 51502; SRPS B.H3.634.

PHYSICAL - CHEMICAL CHARACTERISTICS

Characteristics	Units	Typical values	Test methods
Appearance, color	-	Homogeneous, brown	Visually
NLGI consistency	-	2	-
Type of soap (thickener)		Li	-
Penetration at 25 °C after 60 cycles	mm/10	235	SRPS ISO 2137
Drop point	°C	198	SRPS ISO 2176
Oil extraction	%	9,5	DIN 51 807/1
Temperature interval of application	°C	- 40 do + 120 (shortly on 130)	-
ISO classification	-	L-XDCHA 2	-
DIN classification	-	K 2 K - 40	-

PURPOSE

LITOL-24 is recommended for the lubrication of roller and sliding bearings, slideways, joints, electromotors, mechanical assemblies in every industry at moderate loads, speeds and operating temperatures. It can also be used for the lubrication of motor vehicles, construction and agricultural machinery and other means of transport.

STORAGE

LITOL-24 - should be stored in their original packaging protected from the direct influence of the atmosphere.

PACKAGING:

0.4 kg	0.8 kg	4 kg	5 kg	15 kg	17 kg	180 kg
x 30 pcs	x 8 pcs	x		x	x	x