

DINARA[®] OIL[®]

Vaš kod za ulja i maziva

TECHNICAL INFORMATIONS ABOUT THE PRODUCT MOTOR OILS FOR PASSENGER VEHICLES

LONG LIFE SAE 20W60

LONG LIFE SAE 20W60 is a mineral multigrade engine oil for the lubrication of gasoline and diesel engines of passenger and commercial vehicles, with or without the catalyst and turbocharger in all exploitation conditions. It is recommended for vehicles that have traveled over 50 000 km and have high oil consumption.

Advantages:

- forms a stable and strong oil film;
- ensures stable and adequate oil pressure in the lubrication system;
- eliminates appearance of smoke on the engine exhaust system.

QUALITY LEVEL: API SL/CF; ACEA A2/B3/E2; MB 229.1/228.1

PHYSICAL - CHEMICAL CHARACTERISTICS

Characteristics	Units	Typical values	Test methods
Density on 15 °C	g/cm ³	0,89	SRPS EN ISO 3675
Kinetic viscosity at 100 °C	mm ² /s	22-24	SRPS ISO 3104
Viscosity index	-	120	SRPS ISO 2909
Point of ignition, COC	°C	230	SRPS ISO 2592
Pour point	°C	-22	SRPS ISO 3016
Total base number (TBN)	mgKOH/g	7,5	SRPS ISO 3771
Foaming, max sequence I, sequence I, sequence III	mL/mL	10/0 50/0 10/0	SRPS ISO 6247

PURPOSE

LONG LIFE SAE 20W60 is used for the lubrication of gasoline and diesel engines of older classic passenger and light commercial vehicle designs that have traveled a large number of kilometers (operating hours) over 50 000 km. Oil change is done according to the vehicle manufacturer's recommendations, but the common recommendation is 15 000 km for gasoline engines and 10 000 km for diesel engines.

STORAGE

LONG LIFE SAE 20W60 - should be stored in their original packaging protected from the direct influence of the atmosphere.

PACKAGING:

1 L	5 L	10 L	20 L	200 L	1000 L
x 15 pcs	x 3 pcs			x	x