

DINARA[®] OIL[®]

Vaš kod za ulja i maziva

TECHNICAL INFORMATIONS ABOUT THE PRODUCT ENGINE OIL FOR FOUR STROKE MOTORCYCLE ENGINES AND MOWERS

LUG OIL 4T SAE 30

LUG OIL 4T SAE 30 is a high quality mineral engine oil for the lubrication of four-stroke air-cooled engines of motorcycles, lawn-mowers and similar machines which perform at constant speed.

Advantages:

- provides excellent protection of the engine against wear and corrosion;
- cooling the engine effectively;
- provides maximum engine power and low friction.

QUALITY LEVEL: API SJ; ACEA A3-02/B3;

PHYSICAL - CHEMICAL CHARACTERISTICS

Characteristics	Units	Typical values	Test methods
Density on 15 °C	g/cm ³	0,890	SRPS EN ISO 3675
Kinetic viscosity at 100 °C	mm ² /s	12,0-12,5	SRPS ISO 3104
Point of ignition, COC	°C	220	SRPS ISO 2592
Pour point	°C	- 20	SRPS ISO 3016

PURPOSE

LUG OIL 4T SAE 30 is used for the lubrication of four-stroke engines of the latest generation built in lawn-mowers, motocultivators, trimmers and other machines which constantly perform at high rotational speed with air or oil-cooled engines. Suitable for engines like: Briggs & Stratton, Kubota, Clinton, Honda, Onan, Homelite, Tecumseh, Kawasaki, Wisconsin, Kohler and similar.

STORAGE

LUG OIL 4T SAE 30 - should be stored in their original packaging protected from the direct influence of the atmosphere.

PACKAGING:

0.6 L	1 L	5 L	10 L	200 L	1000 L
x 20 pcs	x 15 pcs			x	x