

# DINARA OIL®

*Vaš kod za ulja i maziva*

## TECHNICAL INFORMATIONS ABOUT THE PRODUCT LUBRICATING GREASES – LITHIUM GREASE

### REDMAST 0

**REDMAST 0** is a special lubricating grease based on lithium soap, specially selected high quality mineral oils additives which provides excellent functional characteristics.

Advantages:

- excellent EP properties;
- excellent adhesion;
- great mechanical stability;
- good rheological properties, suitable for central lubrication.

**QUALITY LEVEL: ISO 6743-9; DIN 51825; DIN 51502; SRPS B.H3.634.**

### PHYSICAL - CHEMICAL CHARACTERISTICS

Characteristics	Units	Typical values	Test methods
Appearance, color	-	homogeneous	Visually
NLGI consistency	-	0	-
Penetration at 25 °C after 60 cycles	mm/10	365	SRPS ISO 2137
Drop point	°C	175	SRPS ISO 2176
Temperature interval of application	°C	- 30 do + 130 (shortly on 140)	-
ISO classification	-	L-XCFEB 0	-
DIN classification	-	KP 0 K - 30	-

### PURPOSE

**REDMAST 0** is recommended for the lubrication of bearings and gears with hand-held electric grinders, saws and drills, and rear bridges of motocultivators. It is suitable for central lubrication, especially suitable for low temperature applications.

### STORAGE

**REDMAST 0** - should be stored in their original packaging protected from the direct influence of the atmosphere.

### PACKAGING:

0.85 kg	4 kg	15 kg	17 kg	180 kg
x 15 pcs				x