

# DINARA OIL®

Vaš kod za ulja i maziva

## TECHNICAL INFORMATIONS ABOUT THE PRODUCT OIL FOR AGRICULTURAL MECHANIZATION

### TRACTOL JD FLUID SAE 10W30

**TRACTOL JD FLUID SAE 10W30** is a mineral tractor oil (UTTO) for the lubrication of hydraulics, transmission and wet brakes of modern middle power and high power tractors.

It has high oxidation stability, high viscosity index and low flow point. It is compatible with all sealants and has excellent filterability even in the presence of water.

Advantages:

- it has high oxidation stability, high viscosity index and low flow point;
- it is compatible with all sealants;
- operates in all weather conditions;
- has excellent filterability even in the presence of water.

**QUALITY LEVEL: API GL-4; JD J20A/J20C; M F M-1135/1141/1143/1145; ALLISON C4; CATERPILLAR TO-2; JI CASE MS 1206/07/09; FORD M2C-86B/134D, SPERRY VICKERS/EATON: I-280-S**

### PHYSICAL - CHEMICAL CHARACTERISTICS

Characteristics	Units	Typical values	Test methods
Density on 15 °C	g/cm <sup>3</sup>	0,87	SRPS EN ISO 3675
Kinetic viscosity at 100 °C	mm <sup>2</sup> /s	9,2-9,5	SRPS ISO 3104
Viscosity index	-	135	SRPS ISO 2909
Point of ignition, COC, min	°C	220	SRPS ISO 2592
Pour point	°C	-30	SRPS ISO 3016
Corrosity (Cu paper, 3h, 150°C)	class	1a	SRPS ISO 2160

### PURPOSE

**TRACTOL JD FLUID SAE 10W30** is primarily used for the lubrication of JOHN DEERE tractors, as well as for other manufacturers' tractors that request this quality level.

It is also used for a new generation of tractors, in which hydraulics, transmission and wet brakes are functionally connected, and the entire system is supplied with the same oil from a common or two chambers the most. Use the product as recommended by the manufacturer. It is not used for engine.

### STORAGE

**TRACTOL JD FLUID SAE 10W30** - should be stored in their original packaging protected from the direct influence of the atmosphere.

### PACKAGING:

1 L	5 L	10 L	20 L	200 L	1000 L
		x 2 pcs		x	x