

DINARA[®] OIL[®]

Vaš kod za ulja i maziva

TECHNICAL INFORMATIONS ABOUT THE PRODUCT OIL FOR AGRICULTURAL MACHINERY

TRAKTOL OIL SAE 20W50

TRAKTOL OIL SAE 20W50 is a mineral engine oil for lubrication of diesel engines of agricultural machinery, tractors, in all climate conditions. It is primarily recommended for engines with increased oil consumption. Ensures reliable operation of the engine under normal and harsh operating conditions, protects the engine from corrosion, reduces engine wear, creates deposits and varnishes thereby ensuring engine cleanliness.

Advantages:

- ensures reliable operation of the engine under normal and harsh operating conditions;
- reduces engine wear, creates deposits and varnishes thereby ensuring engine cleanliness;
- protects the engine from corrosion.

QUALITY LEVEL: API CF-4/SG

PHYSICAL - CHEMICAL CHARACTERISTICS

Characteristics	Units	Typical values	Test methods
Density on 15 °C	g/cm ³	0,89	SRPS EN ISO 3675
Kinetic viscosity at 100 °C	mm ² /s	18,5	SRPS ISO 3104
Viscosity index	-	125	SRPS ISO 2909
Point of ignition, COC	°C	230	SRPS ISO 2592
Pour point	°C	-25	SRPS ISO 3016
Total base number (TBN)	mgKOH/g	9	SRPS ISO 3771

PURPOSE

TRAKTOL OIL SAE 20W50 is an engine oil for the lubrication of diesel engines of agricultural machinery of older classical structures which operate at normal and difficult exploitation conditions.

Oil change is done according to the vehicle manufacturer's recommendation, but the common recommendation is after 10 000 km.

STORAGE

TRAKTOL OIL SAE 20W50 - should be stored in their original packaging protected from the direct influence of the atmosphere.

PACKAGING:

1 L	5 L	10 L	20 L	200 L	1000 L
		x 2 pcs		x	x