

DINARA OIL®

Vaš kod za ulja i maziva

TECHNICAL INFORMATIONS ABOUT THE PRODUCT OIL FOR AGRICULTURAL MECHANIZATION

TRACTOL OIL 80

TRACTOL OIL 80 is a multifunctional mineral tractor oil (UTTO) for the lubrication, strength transmission and cooling of small and middle power tractors which use the same oil for transmission, hydraulic system and wet brakes.

Advantages:

- provides excellent lubrication and prevents wear of all moving parts in all exploitation conditions;
- it controls wet brakes friction which provides safe braking;
- has a good filterability in the presence of water;
- excellent compatibility with all sealants.

QUALITY LEVEL: API GL-4; M F M-1139/1145; ALLISON C4; CATERPILLAR TO-2; FORD M2C-86, John Deere JDM J20C

PHYSICAL - CHEMICAL CHARACTERISTICS

Characteristics	Units	Typical values	Test methods
Density on 15 °C	g/cm ³	0,88	SRPS EN ISO 3675
Kinetic viscosity at 100 °C	mm ² /s	14,5	SRPS ISO 3104
Kinetic viscosity at 40 °C	-	95	SRPS ISO 2909
Viscosity index	°C	230	SRPS ISO 2592
Point of ignition, COC	°C	-23	SRPS ISO 3016
Corrosity (Cu paper, 3h, 150°C)	class	1a	SRPS ISO 2160

PURPOSE

TRACTOL OIL 80 is used for the lubrication of power transmission systems, hydraulics and cooling systems of low and medium power tractors which use the same oil, as a recommendation from the manufacturer, for transmission, hydraulics and wet brakes, as well as for other agricultural and construction machinery and implement machines.

STORAGE

TRACTOL OIL 80 - should be stored in their original packaging protected from the direct influence of the atmosphere.

PACKAGING:

1 L	5 L	10 L	20 L	200 L	1000 L
x 15 pcs	x 3 pcs	x 2 pcs		x	x