

DINARA OIL®

Vaš kod za ulja i maziva

TECHNICAL INFORMATIONS ABOUT THE PRODUCT MOTOR OILS FOR PASSENGER VEHICLES

UNIVESAL SAE 15W40, SAE 20W50

UNIVERSAL SAE 15W40, SAE 20W50 are a high quality mineral multigrade engine oils for the lubrication of modern gasoline and diesel engines of passenger vehicles and light commercial vehicles of the latest generation. Also for a light trucks, with or without turbocharger.

Advantages:

- good detergent dispersant properties;
- provides good protection against the formation of sediments and deposits;
- effectively protects the engine from wear and corrosion;
- good oxidation and thermal stability, low oil consumption;
- good low temperature properties.

QUALITY LEVEL: API SJ/CG-4/CF: ACEA A2/A3/B2/B3/C3; MB: 228.1, MB 229.1, VW 500.00, VW 505.00, VOLVO VDS

PHYSICAL - CHEMICAL CHARACTERISTICS

Characteristics	Units	Typical values		Test methods
		SAE 15W40	SAE 20W50	
Density on 15 °C	g/cm ³	0,88	0,89	SRPS EN ISO 3675
Kinetic viscosity at 100 °C	mm ² /s	14,5	18,5	SRPS ISO 3104
Viscosity index	-	135	130	SRPS ISO 2909
Point of ignition, COC	°C	220	230	SRPS ISO 2592
Pour point	°C	-35	-27	SRPS ISO 3016
Total base number (TBN)	mgKOH/g	9	9	SRPS ISO 3771

PURPOSE

UNIVERSAL SAE 15W40, SAE 20W50 are an engine oils with the wide range of use, intended for the lubrication of modern gasoline, diesel and turbo diesel engines of passenger and light commercial vehicles. Provides lower oil consumption, extended drain intervals and better engine performance. Oil change is done according to the vehicle manufacturer's recommendations, but the common recommendation is 15 000 km.

STORAGE

UNIVERSAL SAE 15W40, SAE 20W50 - should be stored in their original packaging protected from the direct influence of the atmosphere.

PACKAGING:

1 L	5 L	10 L	20 L	200 L	1000 L
x 15 pcs				x	